WHAT IS CLAIMED IS:

1. An injecting and sealing apparatus of a liquid crystal display device comprising:

an elevator conveying a liquid crystal display panel having a liquid crystal injection hole from the injecting apparatus to the sealing apparatus;

a residual liquid crystal remover removing contaminated liquid crystal at a periphery of the liquid crystal injection hole;

a sealer sealing the liquid crystal injection hole with a sealant; and an ultraviolet irradiating unit hardening the sealant.

- 2. The apparatus of claim 1, further comprising at least one buffer buffering a time difference between the injecting apparatus and the sealing apparatus.
- 3. The apparatus of claim 1, further comprising a seal-confirming unit confirming a seal state of the liquid crystal display panel.
 - 4. The apparatus of claim 1, wherein the injecting apparatus includes:
 - a loader loading the liquid crystal display panel;
 - a pre-heater heating the liquid crystal display panel;
- a vacuum unit causing an interior of the liquid crystal display panel to be in a vacuum state; and
 - an injector injecting liquid crystal into the liquid crystal display panel.
 - 5. The apparatus of claim 4, wherein the pre-heater includes:
 - a first pre-heater activating contaminants of the liquid crystal; and
 - a second pre-heater heating the liquid crystal display panel.
 - 6. The apparatus of claim 4, wherein the injector includes;
 - a first injector placing the liquid erystal display panel in an atmospheric state; and
 - a second injector-injecting liquid crystal into the liquid crystal display panel.

- 7. The apparatus of claim 1, wherein the residual liquid crystal remover includes: a liquid crystal removing unit removing the contaminated liquid crystal; and a vacuum line evacuating the contaminated liquid crystal.
- 8. The apparatus of claim 7, wherein the vacuum line is provided at a rear side of the liquid crystal removing unit.
 - 9. The apparatus of claim 1, wherein the sealer includes: a roller sealing the liquid crystal injection hole; a sealant box filled with a sealant; and a leveler maintaining a thickness of the sealant.
- 10. A method of injecting and sealing a liquid crystal display panel comprising:

 conveying a plurality of liquid crystal display panels from an injecting apparatus to a sealing apparatus; and

sealing and hardening liquid crystal injection holes of the liquid crystal display panels using a roller.

- 11. The method of claim 10, wherein said sealing includes sealing the injection holes in a downward state.
 - 12. The method of claim 10, wherein the injecting apparatus includes:
 - a loader loading the liquid crystal display panel;
 - a pre-heater heating the liquid crystal display panel;
- a vacuum unit causing an interior of the liquid crystal display panel to be in a vacuum state; and
 - an injector injecting liquid crystal into the liquid crystal display panel.
 - 13. The method of claim 10, wherein the sealing apparatus includes:

 a buffer buffering a time difference between the injecting apparatus and the sealing

12

apparatus;

a residual liquid crystal remover removing contaminated liquid crystal at a periphery of the liquid crystal injection hole;

a sealer sealing the liquid crystal injection hole with a sealant; and an ultraviolet irradiating unit hardening the sealant.

- 14. The method of claim 13, wherein the contaminated liquid crystal is removed by an N_2 blow system.
- 15. The method of claim 13, wherein the contaminated liquid crystal is removed by a vacuum system.
- 16. The method of claim 10, wherein said hardening includes irradiating an ultraviolet ray by a lamp scanning system.
- 17. The method of claim 16, wherein the liquid crystal injection holes collectively harden by the lamp scanning system.